

# **2024 KPP 8500 ANYTHING Street Legal Diesel RULES**

This class is designed for daily-driven, on the road pickup trucks (full-bodied Diesel pickup trucks).  
**Valid DOT registration license plates and insurance are mandatory.**

1. **WEIGHT:** 8500 lbs. Weight is with driver. Plus or minus 100 lbs at Track official's discretion.
2. **BALLAST:** Ballast is permitted. Hanging weights are prohibited. Ballast may be added in the bed of the truck. If used, ballast must be securely fastened to the bed.
3. **BATTERIES:** The batteries must be securely mounted with a hold down strap. They may not be located in the driver compartment or forward of the radiator core support. **BODY:** The body must be the OEM truck body, including the full bed floor. The body must retain full sheet metal. Metal aftermarket hoods are permitted. Fiberglass is prohibited. The hood must be closed and securely latched while the vehicle is hooked to the sled. The complete OEM firewall and OEM floor pan is mandatory.
4. **INTERIOR:** A complete interior, including dashboard, door panels, headliner, etc., is mandatory. Two matching front seats are mandatory. Aftermarket seats are permitted; they must be fully upholstered. All factory controls (lights, signals, horn, windows, wipers, etc.) must be retained and be operative. The use of hand-throttle controls is prohibited.
5. **STEERING:** The vehicle must retain the full, original OEM steering gear. The vehicle must retain the original OEM power steering assistance, if it was so equipped. Additional stabilizers are permitted. Non-OEM power assist methods are prohibited.
6. **STREET EQUIPMENT:** Complete headlight and taillight assemblies (all) are mandatory and must be operative. Complete OEM windshield and windows are mandatory. Windows must be operative per factory specifications; that is, they must open and close via OEM electrical or mechanical means.
7. **BRAKES:** Four-wheel hydraulic brakes are mandatory.
8. **CHASSIS:** The OEM chassis is mandatory. The engine must be in the OEM location for the body used. The vehicle must retain the full OEM chassis. Wheel tubs, back-half conversions, tube chassis, etc., are prohibited.
9. **COOLING SYSTEM:** Radiators must be in the stock location and be of at least stock size.
10. **CREDENTIALS:** All drivers must have a valid state driver's license.
11. **DRIVELINE:** An OEM transmission and transfer case are mandatory. They must have been an option on a one-ton or smaller pickup.
12. **DRIVER RESTRAINT SYSTEM:** The OEM restraint system is mandatory and must be worn.

13. **ENGINE:** The engine is limited to a stock-appearing, OEM make-specific compression ignition engine. NITROUS OXIDE is prohibited along with other oxygen extenders as well as the use of PROPANE is also prohibited. All system components MUST be removed from the truck.
14. **EXHAUST:** All vehicles must be equipped to direct exhaust upward. The exhaust must exit rearward of the driver's compartment. If the muffler or catalytic converter has been changed from stock, two 3/8 inch diameter bolts must be placed through the exhaust pipe in a cross pattern within one inch of each other and must be within 12" of the exhaust housing. FIRE
15. **EXTINGUISHER SYSTEM:** A fire extinguisher system is permitted. It must be securely mounted.
16. **FUEL & FUEL SYSTEM:** The fuel must be pump #1/#2 diesel only. Soy/Bio-diesel fuel is permitted. The OEM fuel tank is mandatory and must be used. Racing fuel cells are prohibited and must be removed from the vehicle.
17. **FUEL INJECTION PUMP:** The fuel injection pump is limited to a stock-appearing, OEM engine model-specific pump only. The use of multiple high-pressure common-rail fuel pumps is prohibited. Powerstroke engines with a single factory turbo may utilize a second HPOP. Pumps from different years in the same engine model may be interchanged.
18. **HITCH:** The hitch must be a receiver-style hitch; reinforcements are permitted. Reinforcements must not extend forward of the centerline of the rear axle. Trick hitches are prohibited. The hooking point must be the rear-most point on the vehicle and must be rearward of the stock location of the tailgate. The hitch must be horizontal to the ground and stationary in all directions. Bumpers may be notched or removed. The hitch's height from the ground may not exceed 26 inches The hooking point must have a minimum 3.00 inch wide x 3 3/4 length inside diameter opening for the sled hook. The hooking point will be measured to the center of the clevis loop.
19. **REAR END:** Non-OEM rear-end housings are prohibited. It must have been an option on a one-ton or smaller pick up.
20. **SUSPENSION, FRONT:** The upper mounting point for strut assemblies must be in the factory location. Adjustable caster/camber pillow ball mounts are permitted. The lower control arm may be strengthened provided factory-mounting points to chassis are maintained. The lower mounting point for the strut assembly may be modified for improved caster or camber. Strut tower braces, lower tie bars, sway bars, and limit straps are permitted. Traction bars and devices are permitted.
21. **SUSPENSION, REAR:** An OEM-style suspension is mandatory. Traction bars and devices are permitted; they must be Bolt on only; welds are permitted for attachment to frame or axle housing. Control arms may be strengthened or replaced, provided all original mounting points are retained. Sway bars and limit straps are permitted. All rear suspensions must use at least one working shock absorber per wheel. Blocked suspension is prohibited. Suspension must have at least 1" of working travel.
22. **TIRES:** The tires must be DOT street tires. Cut tires are prohibited.

23. **TRANSFER CASE:** Non-OEM transfer cases are prohibited. The transfer case must have been an option on a one ton or smaller pick up truck.
24. **TRANSMISSION, AUTOMATIC:** Non-OEM transmissions are prohibited. Aftermarket torque converters, valve bodies and internal components are permitted. Transmission brakes are prohibited. Any non-OEM floor mounted automatic transmission shifter must be equipped with a spring-loaded positive reverse lockout device to prevent the shifter from accidentally being put into reverse gear. A functional neutral safety switch is mandatory. All transmission lines must be metallic or high-pressure-type hose.
25. **TRANSMISSION, MANUAL:** Non-OEM transmissions are prohibited. Aftermarket internal components are permitted. All manual transmissions must be clutch assisted. Sequential shifters are prohibited.
26. **TURBOCHARGER:** The turbocharger is limited to a stock ONLY, OEM/Factory make-specific chargers. Turbochargers from different years in the same make may NOT be interchanged. 6.4 liter Powerstroke engines may utilize the factory twin-turbo configuration.
27. **WATER INJECTION:** Water injection is prohibited. All system components must be removed from the truck.
28. **WHEELBASE:** The vehicle must retain the original factory wheelbase and track width. Rear dual wheels are allowed